

# CELESTION

## Legacy Pro Audio

### NTR10-2520D



### 10-inch cast aluminium chassis, neodymium magnet mid/ bass driver

- Vented cast aluminium heatsink
- Compact high flux Dual Magnet Motor design

**500W**

Continuous power rating

**96dB**

sensitivity

**2.5in**

Copper clad aluminium coil voice

#### General Specifications

Nominal Diameter	254mm / 10in
Power Rating	250W
Continuous power rating	500W
Rated impedance	8 ohm
Sensitivity	96dB
Frequency range	55-3500Hz
Chassis type	Cast aluminium
Magnet type	Neodymium
Voice coil diameter	64mm / 2.5in
Voice coil material	Copper clad aluminium
Former material	Glass fibre
Cone material	Kevlar loaded paper
Surround material	Cloth-sealed
Suspension	Single
Gap height (Hg)	8mm / 0.32in
VC winding height (Hvc)	16mm / 0.63in

#### Mounting Information

Overall diameter	260mm / 10.24in
Overall depth	113mm / 4.45in
Cut-out diameter	235mm / 9.25in
Mounting hole dimensions	7.5x6.5mm / 0.3x0.26in
Number of mounting holes	4
Mounting hole PCD	244-247mm / 9.6-9.7in
Unit weight	2.2kg / 4.9lb

#### Packed Dimensions & Weight

Single pack size W x D x H	305mm x 305mm x 150mm / x 12.0in 12.0in x 5.9in
Single pack weight	2.5kg / 5.5lb
Multi pack qty	96
Multi pack size W x D x H	1080mm x 880mm x 840mm / 42.5in x 34.6in x 33.1in
Multi pack weight	235kg / 518lb

#### Frequency Response and Impedance Curves

#### Parameters

Sd	346.36cm <sup>2</sup> / 53.69in <sup>2</sup>
Fs	57.20Hz
Mms	37.93g / 1.34oz
Qms	2.824
Qes	0.322
Qts	0.289
Re	5.92 ohm
Vas	34.69l / 1.23ft <sup>3</sup>
Bl	15.83Tm
Cms	0.20mm/N
Rms	4.82kg/s
Le (at 1kHz)	0.49mH
Xmax	4mm / 0.16in



