


FTR15-4080HD



- 15" ferrite woofer provides 1000Wrms power handling (AES Standard) and 95dB sensitivity
- 4" high temperature Inside/Outside voice coil efficiently dissipates heat, preventing sensitivity loss through thermal compression
- FlexirolTM technology for greater excursion control
- Double suspension for exceptional linearity at the highest excursions
- Optimised for very long throw applications
- Smart chassis design minimises acoustic distortion

8 Frequency Response



1. Tested for two hours using a continuous, band-limited pink noise signal as per AES standard. Power calculated on minimum impedance. Loudspeaker tested in free air.
2. Continuous Power Handling is defined as 3dB greater than the AES rating.
3. Measured on axis at 1W, 1m in 2 anechoic environment.
4. Xmax derived from: (voice coil winding width-gap depth)/2.
5. Small signal parameters measured after unit subjected to pre-conditioning signal.

General Specifications

Nominal diameter	381mm/15in
Power rating ¹	1000Wrms
Continuous power rating ²	2000W
Nominal impedance	8
Sensitivity ³	95dB
Frequency range	35-2500Hz
Voice coil diameter	100mm/4in
Chassis type	Cast Aluminium
Magnet type	Ferrite
Magnet weight	3.1kg/110oz
Coil material	Round copper
Former material	Glass fibre
Cone material	Glass loaded paper with weather-resistant impregnation
Surround material	Cloth-sealed
Suspension	Double
Xmax ⁴	8mm/0.33in
Gap depth	9.5mm/0.37in
Voice coil winding width	25mm/0.98in

Small Signal Parameters

D	0.33m/12.99in
Fs	37.1Hz
Mms	130.4g/4.6oz
Qms	4.67
Qes	0.33
Mmd	116.25g/4.10oz
Qts	0.31
Re	5.89Ω
Vas	146.29lt/5.16ft ³
Bl	23.15Tm
Cms	0.14mm/N
Rms	6.51Kg/s
Le (at 1kHz)	1.59mH

Mounting Information

Overall diameter	385mm/15.16in
Overall depth	173mm/6.81in
Cut-out diameter	351mm/13.82in
Mounting slot dimensions	10mm x 7mm/0.39in x 0.27in
Number of mounting slots	8
Mounting PCD range	365-375mm/14.37-14.76in
Unit weight	9.5kg/20.9lb

Packed Dimensions & Weight

Single pack size W x D x H	435mm x 435mm x 200mm /17.1in x 17.1in x 7.9in
Single pack weight	10.8kg/23.8lb
Multi pack size W x D x H	435mm x 435mm x 200mm /17.1in x 17.1in x 7.9in
Multi pack weight	10.8kg/23.8lb