

## HF Compression Drivers

### CDX14-3035

### 1.4in exit, ferrite magnet, single piece titanium diaphragm HF compression driver

- Single piece titanium diaphragm and surround
- Enhanced surround shape for greater linearity
- High temperature polymer clamp ring minimises distortion

**240W**

Continuous power rating

**108dB**

sensitivity

**3in**

Edgewound clad copper voice aluminium coil



#### General Specifications

Power Rating	120W
Continuous power rating	240W
Rated impedance	8 ohm
Sensitivity	108dB
Frequency range	500-20,000Hz
Recommended min. crossover (12 dB/oct)	800
Magnet type	Ferrite
Voice coil diameter	75mm / 3in
Voice coil material	Edgewound copper clad aluminium
Diaphragm material	Titanium
Surround material	Titanium

#### Mounting Information

Width	180mm / 7in
Depth	69mm / 2.7in
Fitting	Bolt (4 x M6 holes on a 102mm/4in PCD)
Throat exit	35mm / 1.4in
Unit weight	5.4kg / 11.9lb

#### Packed Dimensions & Weight

Single pack size W x D x H	240mm x 200mm x 100mm / x 9.4in 8in x 4in
Single pack weight	6kg / 12.2lb

#### Frequency Response and Impedance Curves

