

## Coaxial Loudspeakers

### FTX1530



## 15-inch cast aluminium chassis, ferrite magnet coaxial driver

- Ferrite magnet assembly acts as common motor for both LF and HF
- Titanium HF diaphragm
- Demodulation ring
- 90° nominal HF coverage
- HF repair kit available

**800W**

Continuous power rating

**97dB**

sensitivity

**3in**

Edgewound clad copper voice aluminium coil

**3in**

#### General Specifications

Nominal Diameter	381mm / 15in
Power Rating	400W
Continuous power rating	800W
Rated impedance	8 ohm
Sensitivity	97dB
Frequency range	40-4000Hz
Chassis type	Cast aluminium
Magnet type	Ferrite
Magnet weight	2.3kg / 81oz
Voice coil diameter	75mm / 3in
Voice coil material	Edgewound copper clad aluminium
Former material	Glass fibre
Cone material	Kevlar loaded paper
Surround material	Cloth-sealed
Suspension	Single
Gap height (Hg)	8mm / 0.31in
VC winding height (Hvc)	16mm / 0.63in

#### Mounting Information

Overall diameter	387mm / 15.24in
Overall depth	176mm / 6.93in
Cut-out diameter	351mm / 13.82in
Mounting hole dimensions	10x7mm / 0.39x0.27in
Number of mounting holes	8
Mounting hole PCD	365-375mm / 14.37-14.76in
Unit weight	6.5kg / 14.3lb

#### Parameters

Sd	855.30cm <sup>2</sup> / 132.57in <sup>2</sup>
Fs	42.50Hz
Mms	84.29g / 2.97oz
Qms	3.809
Qes	0.297
Qts	0.276
Re	5.36 ohm
Vas	172.07l / 6.08ft <sup>3</sup>
Bl	20.16Tm
Cms	0.17mm/N
Rms	5.91kg/s
Le (at 1kHz)	0.82mH
Xmax	6mm / 0.24in

#### Additional HF Specifications

Power rating	75W
Continuous power rating	150W
Rated impedance	8 ohm
Sensitivity	106.5dB
Frequency range	800-18,000Hz
Recommended min. crossover 12d	1000Hz
B/oct	
Voice coil diameter	75mm / 3in
Magnet type	Dual-ferrite magnet motor
Diaphragm material	Titanium
Surround material	Polyimide

#### Packed Dimensions & Weight

Single pack size W x D x H	428mm x 428mm x 228mm / x 16.8in 16.8in x 8.9in
Single pack weight	11kg / 24.2lb
Multi pack qty	36
Multi pack size W x D x H	1050mm x 1200mm x 950mm / 41.3in x 47.2in x 37.4in
Multi pack weight	360kg / 794lb







