

1-inch exit neodymium magnet compression driver

- Aluminium diaphragm with elastomer surround
- Copper inductance sleeve for improved HF performance
- 2,500Hz recommended min. crossover freq (12dB/oct)

40W

Continuous power rating

104dB

sensitivity

1.4in

Copper clad aluminium coil voice

General Specifications

Power Rating	20W
Continuous power rating	40W
Rated impedance	8 ohm
Sensitivity	104dB
Frequency range	2000-20,000Hz
Recommended min. crossover (12 dB/oct)	2500Hz
Magnet type	Neodymium
Voice coil diameter	35mm / 1.4in
Voice coil material	Copper clad aluminium
Diaphragm material	Aluminium
Surround material	Elastomer

Mounting Information

Width	90mm / 3.5in
Depth	57mm / 2.2in
Fitting	Bolt (2 x M6 holes on 76mm/3.0in PCD)
Throat exit	25mm / 1in
Unit weight	0.25kg / 0.6lb

Packed Dimensions & Weight

Single pack size W x D x H	90mm x 90mm x 60mm / x x 3.5in 3.5in 2.4in
Single pack weight	0.5kg / 1.1lb
Multi pack qty	24
Multi pack size W x D x H	250mm x 350mm x 290mm / x 9.8in 13.8in x 11.4in
Multi pack weight	7kg / 14.5lb

Horns and repair kits

T5503	Diaphragm repair kit 8 ohm
T5359	H19040P Horn
T5134	H17050 No Bell Horn

