

- Glass loaded paper cone with weather-resistant impregnation
- Airflow vented magnet assembly for dynamic heat dispersion

1200W

Continuous  
power rating

97dB

sensitivity

4in

Round copper  
voice coil

General Specifications

Nominal Diameter	457mm / 18in
Power Rating	600W
Continuous power rating	1200W
EIA power rating	800W
Rated impedance	8 ohm
Sensitivity	97dB
Frequency range	30-3000Hz
Chassis type	Cast aluminium
Magnet type	Ferrite
Magnet weight	3.1kg / 110oz
Voice coil diameter	100mm / 4in
Voice coil material	Round copper
Former material	Glass fibre
Cone material	Glass loaded paper (weather-resistant)
Surround material	Cloth-sealed
Suspension	Single
Gap height (Hg)	10mm / 0.39in
VC winding height (Hvc)	22mm / 0.87in

Mounting Information

Overall diameter	452mm / 17.8in
Overall depth	205mm / 8.1in
Cut-out diameter	416mm / 16.38in
Mounting hole dimensions	10x7mm / 0.39x0.27in
Number of mounting holes	8
Mounting hole PCD	429-440mm / 16.89-17.32in
Unit weight	9.7kg / 21.4lb

Parameters


Sd	1134.12cm <sup>2</sup> / 175.79in <sup>2</sup>
Fs	32.50Hz
Mms	155.60g / 5.49oz
Qms	4.334
Qes	0.335
Qts	0.311
Re	5.32 ohm
Vas	281.30l / 9.93ft <sup>3</sup>
Bi	22.48Tm
Cms	0.15mm/N
Rms	7.34kg/s
Le (at 1kHz)	1.25mH
Xmax	6mm / 0.24in

Packed Dimensions & Weight

Single pack size W x D x H	500mm x 500mm x 240mm / x 19.7in 19.7in x 9.4in
Single pack weight	11.4kg / 25.1lb
Multi pack qty	24
Multi pack size W x D x H	1210mm x 1050mm x 980mm / 47.6in x 41.3in x 35.4in
Multi pack weight	265kg / 580lb



Frequency Response and Impedance Curves



**Power rating:** Tested for two hours using a continuous, band-limited pink noise signal as per AES standard. Power calculated on minimum impedance. Loudspeaker tested in free air.

**Continuous power rating:** Defined as 3dB greater than the AES rating.

**Sensitivity:** Measured on axis at 1W, 1m in 2 pi anechoic environment.

**Parameters:** Measured after unit subjected to pre-conditioning signal.

**Xmax:** Hvc-Hg/2