

CELESTION

Legacy Pro Audio

FTR15-4080HDX



15-inch, cast aluminium chassis, ferrite magnet LF driver

- Glass loaded paper cone with weather-resistant impregnation
- Optimised double suspension
- Airflow vented magnet assembly for dynamic heat dispersion

2000W

Continuous power rating

96dB

sensitivity

4in

Round copper voice coil

General Specifications

Nominal Diameter	381mm / 15in
Power Rating	1000W
Continuous power rating	2000W
Rated impedance	8 ohm
Sensitivity	96dB
Frequency range	40-2500Hz
Chassis type	Cast aluminium
Magnet type	Ferrite
Magnet weight	3.1kg / 110oz
Voice coil diameter	100mm / 4in
Voice coil material	Round copper
Former material	Glass fibre
Cone material	Glass loaded paper (weather-resistant)
Surround material	Cloth-sealed
Suspension	Double
Gap height (Hg)	9.5mm / 0.37in
VC winding height (Hvc)	25mm / 0.99in
Additional impedances	4 ohm

Mounting Information

Overall diameter	385mm / 15.16in
Overall depth	180mm / 7.1in
Cut-out diameter	351mm / 13.82in
Mounting hole dimensions	10x7mm / 0.39x0.27in
Number of mounting holes	8
Mounting hole PCD	365-375mm / 14.37-14.76in
Unit weight	9.7kg / 21.3lb

Packed Dimensions & Weight

Single pack size W x D x H	435mm x 435mm x 200mm / x 17.1in 17.1in x 7.9in
Single pack weight	11.5kg / 25.4lb
Multi pack qty	36
Multi pack size W x D x H	1210mm x 1050mm x 980mm / 47.6in x 41.3in x 35.4in
Multi pack weight	380kg / 835lb

Frequency Response and Impedance Curves

Parameters

Sd	855.30cm ² / 132.57in ²
Fs	40.00Hz
Mms	147.45g / 5.20oz
Qms	3.089
Qes	0.357
Qts	0.320
Re	5.12 ohm
Vas	111.20l / 3.93ft ³
Bl	23.07Tm
Cms	0.11mm/N
Rms	13.77kg/s
Le (at 1kHz)	1.73mH
Xmax	10.1mm / 0.4in



