## CELESTION

# LF Loudspeakers **TF0410MR**



#### **Mounting Information**

Overall diameter Overall depth Cut-out diameter Mounting hole dimensions Number of mounting holes Mounting hole PCD Unit weight


120x108.5mm / 4.7x4.3in

60mm / 2.4in 95mm / 3.7in 4.3mm / 0.17in

109mm / 4.3in

1.2kg / 2.6lb

## Frequency Response and Impedance Curves



**Power rating:** Tested for two hours using a continuous, band-limited pink noise signal as per AES standard. Power calculated on minimum impedance. Loudspeaker tested in free air.

Continuous power rating: Defined as 3dB greater than the AES

rating.

Sensitivity: Measured on axis at 1W, 1m in 2 pi anechoic

## 4-inch pressed steel chassis, ferrite magnet midrange driver

Closed back midrange unit

**60W** 90dB 1-inch Round copper Continuous sensitivity power rating voice coil

## **General Specifications**

Nominal Diameter 100mm / 4in Power Rating 30W Continuous power rating 60W 50W EIA power rating Rated impedance 8 ohm Sensitivity 90dB Frequency range 400-10,000Hz Chassis type Pressed steel Magnet type Ferrite Magnet weight 0.37kg / 13oz Voice coil diameter 25mm / 1in Round copper Voice coil material Former material Polyimide Cone material Kevlar loaded paper Surround material Treated paper Suspension Single

### **Parameters**

Fs 461Hz 5.38 ohm Le (at 1kHz) 0.07mH

## Packed Dimensions & Weight

120mm x 120mm x 80mm / x Single pack size W x D x H 4.7in 4.7in x 3.2in

Single pack weight 1.7kg / 3.8lb Multi pack qty

Multi pack size W x D x H 425mm x 280mm x 165mm / x

16.7in 11.0in x 6.5in

Multi pack weight 20kg / 44lb

