


BN10-200X



Light in weight but certainly not in performance the BN10-200X neodymium bass speaker delivers a rich warm tone combined with a powerful low end punch.

8 Frequency Response



General Specifications

Nominal Diameter	254mm / 10in
Power Rating	200W
Rated impedance	8 Ω
Sensitivity	96dB
Magnet type	Neodymium
Voice coil diameter	50.8mm / 2in
Voice coil material	Copper
Former material	Polyimide
Cone material	Kevlar loaded paper
Surround material	Cloth-sealed
Frequency range	45-3500Hz
Xmax	4mm / 0.15in
Gap height (Hg)	8mm / 0.31in
VC winding height (Hvc)	16mm / 0.62in

Mounting Information

Cut-out diameter	229mm / 9in
Diameter	256mm / 10.1in
Mounting hole dimensions	6x8mm / 0.24x0.31in
Mounting hole PCD	245mm / 9.6in
Number of mounting holes	8
Chassis depth (inc gasket )	77mm / 3.02in
Magnet depth	35mm / 1.38in
Overall depth	112mm / 4.4in
Unit weight	1.5kg / 3.3lb

Parameters

Sd	346.4cm2 / 53.69in2
Fs	50.7Hz
Mms	32.21g / 1.14oz
Qms	3.67
Qes	0.297
Qts	0.274
Re	59 Ω
Vas	52l / 1.84ft3
Bi	14.29Tm
Cms	0.306mm/N
Rms	2.79kg/s
Le (at 1kHz)	0.63mH
Xmax	4mm / 0.15in