

## Axiperiodic Drivers

### Axi2050

2-inch exit, neodymium magnet, wide bandwidth Axiperiodic driver



- No midband crossover required
- Low mass Ti diaphragm with unique circumferentially Axiperiodic geometry
- Sculpted diaphragm profile prevents break-up in critical listening band
- Vibration modes decoupled from acoustic modes removing unwanted resonance peaks
- Large effective surround area extends low frequency performance


### General Specifications

Power Rating	150W
Continuous power rating	300W
Rated impedance	8 $\Omega$
Sensitivity	108dB
Frequency range	300-20,000Hz
Magnet type	Neodymium
Voice coil diameter	125mm / 5in
Voice coil material	Aluminium
Diaphragm material	Titanium
Surround material	Integrated


### Mounting Information

Width	198mm / 7.8in
Depth	111mm / 4.4in
Fitting	Bolt (4 x M6 holes on 102mm/4in PCD)
Throat exit	50mm / 2in
Unit weight	7.5kg / 16.5lb

## Frequency Response and Impedance Curves



## Measured - Plane Wave Tube



## Measured - Seos 30 Horn

**Power rating:** Tested for two hours on plane wave tube using a continuous, band-limited pink noise signal as per AES standard. Power calculated on minimum impedance.

**Continuous power rating:** Defined as 3dB greater than the AES rating.

**Sensitivity:** Measured on axis at 1W, 1m, using compatible horn, in 2? anechoic environment.

## Packed Dimensions & Weight

Single pack size W x D x H      300mm x 300mm x 165mm / 11.8in x 11.8in x 6.5in  
Single pack weight              8.2kg / 18.1lb