

LF Loudspeakers

FTR18-4080HDX

18-inch, cast aluminium chassis, ferrite magnet LF driver







- Glass loaded paper cone with weather-resistant impregnation
- Optimised double suspension
- Airflow vented magnet assembly for dynamic heat dispersion

General Specifications

 $\begin{array}{lll} \mbox{Nominal Diameter} & 457\mbox{mm} \, / \, 18\mbox{in} \\ \mbox{Power Rating} & 1000\mbox{W} \\ \mbox{Continuous power rating} & 2000\mbox{W} \\ \mbox{Rated impedance} & 8 \, \Omega \\ \mbox{Sensitivity} & 95\mbox{dB} \\ \mbox{Frequency range} & 30-2500\mbox{Hz} \\ \mbox{Chassis type} & \mbox{Cast aluminium} \end{array}$

Magnet type Ferrite

Magnet weight 3.1kg / 110oz
Voice coil diameter 100mm / 4in
Voice coil material Round copper
Former material Glass fibre

Cone material Glass loaded paper (

weather-resistant)

Surround material Cloth-sealed

Suspension Double

Gap height (Hg) 9.5mm / 0.37in VC winding height (Hvc) 25mm / 0.99in

Mounting Information

Overall diameter 452mm / 17.8in

Overall depth 205mm / 8.1in

Cut-out diameter 416mm / 16.38in

Mounting hole dimensions 10x7mm / 0.4x0.27in

Number of mounting holes


Mounting hole PCD 429-440mm / 16.89-17

.32in

8

Unit weight 9.8kg / 21.6lb

Frequency Response and Impedance Curves



Topmost curve: Frequency response on axis | Secondary curve: Frequency response at 45° off axis

Power rating: Tested for two hours using a continuous, band-limited pink noise signal as per AES standard.

Power calculated on minimum impedance. Loudspeaker tested in free air.

Continuous power rating: Defined as 3dB greater than the AES rating.

Sensitivity: Measured on axis at 1W, 1m in 2 anechoic environment.

Parameters: Measured after unit subjected to pre-conditioning signal.

Xmax: 0.5*(Hvc-Hg) + 0.25*Hg

Parameters

Sd	1134.12cm2 / 175.79i

n 2

Fs 39.20Hz

Mms 171.75g / 6.06oz

 $\begin{array}{c} \text{Qms} & 5.387 \\ \text{Qes} & 0.466 \\ \text{Qts} & 0.429 \\ \text{Re} & 500\,\Omega \end{array}$

Vas 174.88I / 6.18ft 3

 Bi
 21.29Tm

 Cms
 0.10mm/N

 Rms
 7.85kg/s

 Le (at 1kHz)
 1.79mH

Xmax 10.1mm / 0.4in

Packed Dimensions & Weight

Single pack size W x D x H 500mm x 500mm x 240m

m / 19.7in x 19.7in

x 9.4in

Single pack weight 11.6kg / 25.6lb

Multi pack qty 24

Multi pack size W x D x H 1210mm x 1050mm x 98

0mm / 47.6in x 41.3i

n x 35.4in

Multi pack weight 278kg / 608lb

