

## **Legacy Loudspeakers**

# FTR12-4080HDX (Legacy)

12-inch, cast aluminium chassis, ferrite m







- Glass loaded paper cone with weather-resistant impregnation
- Optimised double suspension
- Airflow vented magnet assembly for dynamic heat dispersion

#### **General Specifications**

 $\begin{array}{lll} \mbox{Nominal Diameter} & 305\mbox{mm} \, / \, 12\mbox{in} \\ \mbox{Power Rating} & 1000\mbox{W} \\ \mbox{Continuous power rating} & 2000\mbox{W} \\ \mbox{Rated impedance} & 8 \, \Omega \\ \mbox{Sensitivity} & 93\mbox{dB} \\ \mbox{Frequency range} & 47-3000\mbox{Hz} \end{array}$ 

Chassis type Cast aluminium Magnet type Ferrite

Magnet weight 3.1kg / 110oz
Voice coil diameter 100mm / 4in
Voice coil material Round copper
Former material Glass fibre

Cone material Glass loaded paper (

weather-resistant)

Surround material Cloth-sealed

Suspension Double

Gap height (Hg) 9.5mm / 0.37in VC winding height (Hvc) 25mm / 0.98in

## **Mounting Information**

Overall diameter 313mm / 12.3in
Overall depth 158mm / 6.2in
Cut-out diameter 282mm / 11.1in

Mounting hole dimensions 10x7mm / 0.39x0.27in


Number of mounting holes 8

Mounting hole PCD 291-301mm / 11.7-11.

9in

Unit weight 9.6kg / 21.1lb

#### Frequency Response and Impedance Curves



Topmost curve: Frequency response on axis | Secondary curve: Frequency response at 45° off axis

Power rating: Tested for two hours using a continuous, band-limited pink noise signal as per AES standard.

Power calculated on minimum impedance. Loudspeaker tested in free air.

Continuous power rating: Defined as 3dB greater than the AES rating.

Sensitivity: Measured on axis at 1W, 1m in 2 anechoic environment.

Parameters: Measured after unit subjected to pre-conditioning signal.

Xmax: Hvc-Hg/2

#### **Parameters**

82.29in2

Fs 61.00Hz

Mms 126.30g / 4.46oz

 $\begin{array}{c} \text{Qms} & 2.258 \\ \text{Qes} & 0.479 \\ \text{Qts} & 0.395 \\ \text{Re} & 6.00\,\Omega \end{array}$ 

Vas 21.49I / 0.76ft 3

 Bi
 24.63Tm

 Cms
 0.05mm/N

 Rms
 21.44kg/s

 Le (at 1kHz)
 1.99mH

 Xmax
 8mm / 0.32in

### **Packed Dimensions & Weight**

Single pack size W x D x H 350mm x 350mm x 180m

m / 13.8in x 13.8in

x 7.1in

Single pack weight 11.4kg / 25.1lb

Multi pack qty 36

Multi pack size W x D x H 1210mm x 1050mm x 98

0mm / 47.6in x 41.3i

n x 35.4in

Multi pack weight 375kg / 825lb

