


PULSE XL 15.25



Plenty of clean, deep bass from this heavy-duty 15-inch driver, along with a defined midrange and the smooth treble response that comes with a felt dust dome. With a solid 700W of power handling, the PULSE XL 15.25 delivers an authoritative performance packed with sweet harmonic overtones.

Frequency response



General Specifications

Nominal Diameter	381mm / 15in
Power Rating	700W
Rated impedance	8 Ω
Sensitivity	97dB
Magnet type	Ferrite
Voice coil diameter	63.5mm / 2.5in
Voice coil material	Copper
Former material	Polyimide
Cone material	Cellulose
Surround material	Triple roll, cloth sealed
Frequency range	35-2100Hz
Xmax	8mm / 0.31in
Gap height (Hg)	8mm / 0.3in
VC winding height (Hvc)	20mm / 0.8in

Mounting Information

Cut-out diameter	353mm / 13.9in
Diameter	385mm / 15.15in
Mounting hole dimensions	6.4mm / 0.25in
Mounting hole PCD	370mm / 14.5in
Number of mounting holes	8
Chassis depth (inc gasket)	116.3mm
Magnet depth	13.74in
Overall depth	168mm / 6.6in
Unit weight	5.4kg / 12lb

Parameters

Sd	855.3cm2 / 132.57in2
Fs	33.1Hz
Mms	85.78g
Qms	4.232
Qes	0.525
Qts	0.604
Re	666 Ω
Vas	213.9l / 7.6ft3
Bi	13.88Tm
Cms	0.21mm/N
Rms	4.22kg/s
Le (at 1kHz)	1.32mH
Xmax	8mm / 0.31in