

LF Loudspeakers

FTR08-2011D

8-inch, cast aluminium chassis, ferrite magnet mid/bass driver







- Coated Kevlar-loaded cone for enhanced weather resistance
- Copper sleeved pole reduces HF inductive rise
- Airflow vented magnet assembly for dynamic heat dispersion

General Specifications

 $\begin{array}{lll} \mbox{Nominal Diameter} & 200\mbox{mm / 8in} \\ \mbox{Power Rating} & 200\mbox{W} \\ \mbox{Continuous power rating} & 400\mbox{W} \\ \mbox{EIA power rating} & 350\mbox{W} \\ \mbox{Rated impedance} & 8\ \Omega \\ \mbox{Sensitivity} & 93\mbox{dB} \\ \mbox{Frequency range} & 70-6000\mbox{Hz} \\ \end{array}$

Magnet type Ferrite

Chassis type

Magnet weight 1.2kg / 42oz
Voice coil diameter 50mm / 2in
Voice coil material Round copper
Former material Polyimide

Cone material Kevlar loaded paper

Cast aluminium

Surround material Cloth-sealed

Suspension Single

Gap height (Hg) 8mm / 0.31in VC winding height (Hvc) 15mm / 0.59in

Mounting Information

Overall diameter 225mm / 8.8in

Overall depth 102mm / 4in


Cut-out diameter 187mm / 7.4in

Mounting hole dimensions 6.5mm / 0.26in

Number of mounting holes 8

Mounting hole PCD 210mm / 8.3in
Unit weight 3.65kg / 8lb

Frequency Response and Impedance Curves



Topmost curve: Frequency response on axis | Secondary curve: Frequency response at 45° off axis

Power rating: Tested for two hours using a continuous, band-limited pink noise signal as per AES standard.

Power calculated on minimum impedance. Loudspeaker tested in free air.

Continuous power rating: Defined as 3dB greater than the AES rating.

Sensitivity: Measured on axis at 1W, 1m in 2 anechoic environment.

Parameters: Measured after unit subjected to pre-conditioning signal.

 $\mathsf{Xmax:}\ 0.5^{*}(\mathsf{Hvc}\text{-}\mathsf{Hg}) + 0.25^{*}\mathsf{Hg}$

Parameters

Fs 86.10Hz

Mms 27.75g / 0.98oz

 $\begin{array}{cc} \text{Qms} & 2.238 \\ \text{Qes} & 0.541 \\ \text{Qts} & 0.436 \\ \text{Re} & 5.82\,\Omega \end{array}$

Vas 8.99I / 0.32ft 3

 Bi
 12.71Tm

 Cms
 0.12mm/N

 Rms
 6.71kg/s

 Le (at 1kHz)
 0.38mH

Xmax 5.5mm / 0.22in

Packed Dimensions & Weight

Single pack size W x D x H 226mm x 226mm x 130m

m / 8.9in x 8.9in x

5.1in

Single pack weight 3.8kg / 8.4lb

Multi pack qty 8

Multi pack size W x D x H 470mm x 450mm x 270m

m / 18.5in x 17.7in

x 10.6in

Multi pack weight 31kg / 68lb

