

CDX14-3030 (Legacy)

1.4-inch exit ferrite magnet compression driver



- Single piece titanium diaphragm and surround
- 1,000Hz recommended min. crossover freq (12dB/oct)


General Specifications

Power Rating	100W
Continuous power rating	200W
Rated impedance	8&ohm
Sensitivity	106.5dB
Frequency range	500-20,000Hz
Recommended min. crossover	1000Hz
(12dB/oct)	
Magnet type	Ferrite
Voice coil diameter	75mm / 3in
Voice coil material	Edgewound copper clad aluminium
Diaphragm material	Titanium
Surround material	Titanium


Mounting Information

Width	180mm / 7.0in
Depth	68.0mm / 2.7in
Fitting	Bolt (4 x M6 holes on a 102mm/4in PCD)
Throat exit	35mm / 1.4in
Unit weight	4.9kg / 10.7lb

Frequency Response and Impedance Curves



Measured - Plane Wave Tube



Measured - Exponential Horn 90° x 40° radiation pattern

Power rating: Tested for two hours on plane wave tube using a continuous, band-limited pink noise signal as per AES standard. Power calculated on minimum impedance.

Continuous power rating: Defined as 3dB greater than the AES rating.

Sensitivity: Measured on axis at 1W, 1m, using typical horn, in 2? anechoic environment.

Packed Dimensions & Weight

Single pack size W x D x H 214mm x196mm x 82mm
/ 8.4in x 7.7in x 3.
2in
Single pack weight 5.1kg / 11.2lb

Repair kits

T6509 Diaphragm repair kit 8&ohm

