

LF Loudspeakers

CF0617M

6.5-inch, cast aluminium chassis, ferrite magnet midrange driver



- Inverted dustcap for close positioning of phase plug
- High temperature environmentally robust foam surround
- Copper sleeved pole reduces HF inductive rise
- Chassis design allows for fixing of rear cover

General Specifications

Nominal Diameter 165mm / 6.5in

 $\begin{array}{ll} \mbox{Power Rating} & 200\mbox{W} \\ \mbox{Continuous power rating} & 400\mbox{W} \\ \mbox{Rated impedance} & 8\ \Omega \\ \mbox{Sensitivity} & 96\mbox{dB} \\ \end{array}$

Frequency range 300-7000Hz
Chassis type Cast aluminium

Magnet type Ferrite
Magnet weight 0.6kg / 22oz
Voice coil diameter 45mm / 1.75in

Voice coil material Edgewound copper cla

d aluminium

Former material Glass fibre

Cone material Kevlar loaded paper
Surround material Temperature-resistan

t foam

Suspension Single

Gap height (Hg) 6mm / 0.24in VC winding height (Hvc) 8.4mm / 0.33in

Mounting Information

Overall diameter 189mm / 7.44in (max)
Overall depth 78.5mm / 3.1in
Cut-out diameter 150mm / 5.9in

Mounting hole dimensions 7.5x5.5mm / 0.3x0.22

in


Number of mounting holes 4

Mounting hole PCD 173-175mm / 6.81-6.8

9in

Unit weight 1.9kg / 4.2lb

Frequency Response and Impedance Curves



Topmost curve: Frequency response on axis | Secondary curve: Frequency response at 45° off axis

Power rating: Tested for two hours using a continuous, band-limited pink noise signal as per AES standard. Power calculated on minimum impedance. Loudspeaker tested in free air.

Continuous power rating: Defined as 3dB greater than the AES rating.

Sensitivity: Measured on axis at 1W, 1m in 2 anechoic environment.

Parameters: Measured after unit subjected to pre-conditioning signal.

Xmax: 0.5*(Hvc-Hg) + 0.25*Hg

Parameters

153.94cm2 / 23.86in2

Fs 116.6Hz

Mms 11.59g / 0.41oz

 $\begin{array}{c} \text{Qms} & 6.93 \\ \text{Qes} & 0.481 \\ \text{Qts} & 0.451 \\ \text{Re} & 53 \, \Omega \end{array}$

Vas 5.39I / 0.19ft 3

 Bi
 9.68Tm

 Cms
 0.16mm/N

 Rms
 1.23kg/s

 Le (at 1kHz)
 1.73mH

Xmax 2.7mm / 0.11in

Packed Dimensions & Weight

Single pack size W x D x H 190mm x 190mm x 110m

m / 7.5in x 7.5in x

4.3in

Single pack weight 2.5kg / 5.5lb

Multi pack qty 8

Multi pack size W x D x H 345mm x 345mm x 190m

m / 13.6in x 12.4in

x 7.5in

Multi pack weight 20kg / 44lb

